

FARM MIX

THE PROFESSIONAL MACHINE

Technical data

DRIVE from tractor

- Power requirement 130 – 290 kW (180 – 400 hp)
- Power take-off (1000 rpm) with free-running mechanism
- Mixer drive via fitted hydraulic unit
- Dust filter cleaning by compressed air system from tractor

CHASSIS

- Central drawbar chassis with BWP axle and 2 wheels (tyre size 560/45R22.5)
- 40 km/h version, braked by compressed air
- K80 ball hitch, hydraulic leg support

SIZE / WEIGH

- Length: 5.850 mm
- Width: 2.590 mm
- Height: from 3.500 mm
- Weight: from 6.400 kg

HAMMER MILL HM 500

- Milling performance - 25 te/h
- efficient milling performance - screen area 0.85 m²
- 80 hammers with hard metal
- perforated screen or wire sieving possible



MIXER

- Capacity 6-8 te feed
- tested mixing accuracy
- thick-walled mixing tank of quality steel

MIXER DISCHARGE

- with hose into silo 6 te in 8 - 15 min.
- with feeding arm DN 125 (option)

SUCTION and PRESSURE SYSTEM

- outstanding original from the inventor
- decades of experience
- Tropper Airblock
- conveying hoses ø 90/100 mm

OPERATION AND MAINTENANCE

- foldable sound-absorbing bonnet
- magnetic separator „EASY FIX“
- 160 litre stainless steel hopper for sack-filled goods
- FARM MIX PROFI as standard

LIQUID ADDITION

- with hose 1“
- with Oiltank and counter (option)



Tropper offers you long-term advantages:

- Tested mixing accuracy for your quality assurance
- Simple and robust operation with standard operator terminal FARM MIX PROFI
- Outstanding discharge output by simple routing
- Rapid product change through complete discharge improves your daily output
- Comprehensive personal advice and customer service
- Quick supply of replacement parts (optionally overnight by express courier)

TROPPER Maschinen und Anlagen GmbH.
A-4846 Redlham, Gewerbepark Ost 6

Tel.: 0043/(0)7673/2308-0, Fax: 0043/(0)7673/2308-99
Internet: www.tropper.at, E-mail: office@tropper.at




FARM MIX



**THE PROFESSIONAL
MACHINE THAT
PAYS OFF**

FARM MIX
with 6 - 8 t Mixer
- for more than 5.000 tons a year -





- MMX FarmMix Profi
- visual process control
- 15 function keys
- highly-luminous touch display
- simple operation



- Hammer mill HM 500
- large mill cover
- easy screen change
- 80 hammers with carbide metal for long service lifetime



- Premix hopper 160 litres
- low pour-in height
- for more sacks
- easy to clean
- completely of stainless steel



- Central operating station
- ergonomic operation
- all under control
- stainless steel actuating levers
- optimal work height

- Magnet with Easy Fix
- stainless steel change plate
- easily accessible
- easy to clean
- big aluminium tool box

- Effective 6-8 te mixer
- Equipment height from 3,5m
- 4 load cells each of 22 te capacity
- complete discharge

- Power-Jet filter 140
- large filter surface
- for high suction performance and clean outgoing air

- Sound-absorbing bonnet
- well-designed
- easy to clean
- large aluminium sound insulation cover



- Oil addition as standard
- simple suction lance
- intake by vacuum
- oil counter optional

- Hydraulic system with separate oil circulation
- oil cooler as standard
- big oil tank

- Kaeser suction-pressure blower
- large-volume
- high level of efficiency
- easy switchover S/P

Do you also want your agricultural tractor better use?

The TROPPER FarmMix is a special model of our MMX-Press range. The powerful, towed 6-8 te installation is, due to its compact design (equipment height from 3.5 m) and the flexible drive type via tractor power take-off, a perfect work machine for farmyard feedstuff production.

The heart of this mobile Mill-/Mixing installation is the ORIGINAL SUCTION-PRESSURE mixer from TROPPER. There are now around 500 units operating in 23 different countries across Europe!

Contemporary design and well-rounded sound insulation cover for easy cleaning. The large aluminium bonnet provides an easy access to the powerful main units.

The professional machine with original system

Complete discharge since 1992

TROPPER MMX-Press have been discharged with a simple and efficient system since 1992: Maintenance-free discharge cones ensure optimal mixer emptying without any complex mechanism! As a successful farmer, you need high-quality compound feed – we provide the appropriate tool.

Hammer mill HM 500

The mill is fitted with 80 carbide-tipped hammers, as a standard. Screen change (perforated screen or wire mesh sieve) is possible in the simplest manner.

Thanks to the well-balanced material distribution and the effective fitting of the hammers, milling performances of up to 25 tonnes of grain per hour are not uncommon. Robust construction methods and generously dimensioned bearing for a long lifetime!

